

| Cadillac Escalade | |
|--------------------------------------|----------------|
| Technical Specifications | |
| Dimensions and Capacities | |
| Wheelbase (mm) | 2946 |
| Overall length (mm) | 5151 |
| Width (mm) | 2008 |
| Height (mm) | 1887 |
| Ground clearance (mm) | 212 |
| Curb weight (kg) | 2609 |
| Headroom front/center/rear (mm) | 1044/996/963 |
| Legroom front/center/rear (mm) | 1049/991/650 |
| Shoulder room front/center/rear (mm) | 1659/1656/1567 |
| Hip room front/center/rear (mm) | 1636/1544/1247 |
| Interior cargo volume (l) (SAE) | 3084/1708/478 |
| Fuel tank capacity (l) | 98 |
| Towing capacity – braked (kg) | 3100 |

| Engine and Transmission | |
|---|---|
| Type | L92 Vortec 6.2L V8 with cast-aluminium block and cylinder heads |
| Displacement (cm ³) | 6162 |
| Bore x stroke (mm) | 103.25 x 92 |
| Valvetrain configuration | OHV, 2 valves per cylinder with VVT via dual-equal phaser |
| Fuel system | Sequential fuel injection |
| Compression ratio | 10.5:1 |
| Output (kW/hp/rpm) | 301/409/5700 |
| Peak torque (Nm/rpm) | 565/4300 |
| Fuel consumption 1999/100/EG, urban/extra-urban/total, l/100 km | 23/12.3/16.2 |
| CO ₂ emission, g/km | 383 |
| Maximum speed (km/h) | 170 |
| Transmission type | Hydra-Matic 6L80-E, 6-speed automatic |
| Drive | Full-time 4WD system |
| Gear ratios (:1) | |
| First | 4.027 |
| Second | 2.364 |
| Third | 1.522 |
| Fourth | 1.152 |

| | |
|------------------------------------|---|
| Fifth | 0.852 |
| Sixth | 0.667 |
| Reverse | 3.064 |
| Final drive (axle) ratio | 3.24 |
| Chassis / Suspension | |
| Front | Independent, coil-over-shock, 36-mm stabilizer bar. Road Sensing Suspension, real-time damping |
| Rear | Five-link with coil springs, 28-mm stabilizer bar |
| Traction control | all-speed traction control |
| Steering type | Power-assisted rack and pinion |
| Steering ratio | 17.75:1 |
| Steering wheel turns, lock-to-lock | 3 |
| Turning diameter, curb-to-curb (m) | 11.9 |
| Brakes | |
| Type | Power-assisted four-wheel discs with standard four-channel ABS; vented front discs, solid rear discs; twin-piston front calipers, single-piston rear calipers |
| Rotor diameter x thickness (mm) | Front: 330.2 x 30; Rear: 345 x 20 |
| Wheels | 18-inch x 8-inch 7-spoke machined aluminium (std.) 18-inch x 8-inch 7-spoke chromed aluminium (opt.) |
| Tires | P265/65R18 AL2 Bridgestone (touring) blackwall steel-belted radials |